



MOTOR DATA SHEET

MOTOR PART CODE:

5.523TECAB14-IE3

FRAME SIZE:

132S1-2

| | 50Hz |
|-----------------------|-------------|
| Output (kW) | 5.5 |
| Rotation Speed (rpm) | 2930 |
| Voltage | 400/690 |
| Full Load Current (A) | 10 5.77 |
| Full Load Torque (Nm) | 17.92662116 |

| | 60Hz |
|-----------------------|-----------|
| Output (kW) | 6.6 |
| Rotation Speed (rpm) | 3516 |
| Voltage | 480 828 |
| Full Load Current (A) | 10 5.77 |
| Full Load Torque (Nm) | 14.94 |

Efficiency Data

| 100% | 75% | 50% |
|------|------|------|
| 89.2 | 89.4 | 88.2 |

| | |
|--------------------|---------------|
| Factory Reference | T3A 132S1-2 |
| Tst/Tn (times) | 3.2 |
| Tmax/Tn | 4 |
| Noise (dB) | 80 |
| Moment of inertia | 0.01521165 |
| Type of feet | Not Fitted |
| Protection | IP55 |
| Rotation Direction | F / R |
| Cable Glands | 2 - M25 × 1.5 |
| Paint Colour | RAL 7024 |
| Efficiency | IE3 |
| Bearing (DE) | 6308 2RS C3 |

| | |
|---------------------|----------------|
| Power Factor (cos) | 0.89 |
| Tmin/Tn | 2.5 |
| Ist/In (Times) | 10 |
| Net Weight (Kg) | 43.4 |
| Housing material | Aluminum |
| Insulation Class | F |
| Thermal Protection | PTC 130°C |
| Duty Cycle | S1 |
| Cooling | IC 411 |
| Ambient Temperature | -20°C to +40°C |
| Bearing Brand | NSK |
| Bearing (NDE) | 6208 2RS C3 |

Motors designed and manufactured in accordance with:

IEC 60034
IEC 60038
IEC 60072
2014/30/EU (EMC)
2014/35/EU (LVD)
2011/65/EU (RoHS 2)

www.tecmotors.co.uk

TEC Electric Motors Ltd. reserves the right to amend or change motor designs or data sheet information