



TEC ELECTRIC MOTORS LTD.

Technical Data Sheet

Model T4C 315L1-6

Housing material		Cast Iron
Phase		Three
Frame size		315L
Power(50Hz)	kW	110.00
Current(A)400V	Δ	194.98
Current(A)690V	Y	113.03
Speed(50Hz)	(r/min)	990
Efficiency	IE4	
	Eff.100%	95.80
	Eff.75%	96.00
	Eff.50%	95.60
Power factor cosp	100% load	0.85
60Hz 460/793V	Power(kW)	126.50
60Hz 480/830V	Power(kW)	132.00
Speed(60Hz)	(r/min)	1188
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	1061.11
Tst/Tn (Times)	1.6
Tmax/Tn (Times)	2
Tmin/Tn (Times)	1
Ist/In (Times)	8
Bearings type(DE)	NU319
Bearings type(NDE)	6317C3
Oil seals	95*120*12
Cable glands	2-M63*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	PTC150°C
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	83
Net weight(kg)	1037.00
Moment of inertia (kg*m ²)	6.309021781