



TEC ELECTRIC MOTORS LTD.

Technical Data Sheet

Model **T4C 315M-2**

Housing material		Cast Iron
Phase		Three
Frame size		315M
Power(50Hz)	kW	132.00
Current(A)400V	Δ	222.53
Current(A)690V	Y	129.00
Speed(50Hz)	(r/min)	2980
Efficiency	IE4	
	Eff.100%	96.20
	Eff.75%	96.20
	Eff.50%	95.70
Power factor cosp	100% load	0.89
60Hz 460/793V	Power(kW)	151.80
60Hz 480/830V	Power(kW)	158.40
Speed(60Hz)	(r/min)	3576
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitute		1000 m above sea level

Rated torque(N.m)	423.02
Tst/Tn (Times)	1.8
Tmax/Tn (Times)	2.3
Tmin/Tn (Times)	0.9
Ist/In (Times)	8.5
Bearings type(DE)	6317C3
Bearings type(NDE)	6317C3
Oil seals	85*110*12
Cable glands	2-M63*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	PTC150°C
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	92
Net weight(kg)	1017.00
Moment of inertia (kg*m ²)	2.351992349