TECHNICAL DATA

Three Phase Electric Motors - Aluminum Frame
UMHA 112M-2 IE2
4 kW / 5.5 Cv
2895 RPM



Motor type:	**UMHA 112M-2 IE2**
Output:	**4 kW / 5.5 Cv**
Speed (min^{-1}):	**2895 RPM**
Voltage:	**400 V**
Frequency:	**50 Hz**
Current:	**7.6 A**
Power factor (Cos Ø):	**0.88**
Poles:	**2**
Insulation class:	**F**
Temperature rise Class:	**B**
Efficiency 50%:	**85.2 %**
Efficiency 75%:	**86.3 %**
Efficiency 100%:	**85.8 %**
Torque:	**13.2 N.m**
Tstarting/Tnominal:	**2.3**
Istarting/Inominal:	**8.3**
Tmaximum/Tnominal:	**2.3**
Noise:	**83 Db(A)**
Weight:	**32.5 Kg**
Bearing DE:	**6306 2Z C3**
Bearing NDE:	**6306 2Z C3**

Regime - S1 **Altitude - 1000m** **Environment Temperature - 40ºC**

* References applied only in the UK

CONTACTS:
ACDC Drives Ltd
Units 96 C & D, Blackpole Trading Estate, Blackpole Road,
Worcester, WR3 8TJ

Tel: +44(0) 1905 887 667
Mail: sales@acdcdrives.co.uk

Universal Motors